

INSTRUCTIONS FOR ASSEMBLY AND INSTALLATION**READ AND UNDERSTAND THESE INSTRUCTIONS BEFORE INSTALLING FIXTURE.**

This fixture is intended for installation in accordance with the National Electrical Code and local or federal code specifications. To prevent electrical shock, turn off electricity at fuse box before proceeding.

Retain these instructions for maintenance reference.

INCANDESCENT UNITS

1. Thread **FIXTURE SCREWS** into **UNIVERSAL BAR**.
2. Mount **UNIVERSAL BAR** to **OUTLET BOX** with screws provided in **OUTLET BOX**.
3. Make connections: Black fixture leads or fixture leads without tracer mark to black supply leads; white fixture leads or fixture leads with tracer mark to white supply lead. Use **WIRE NUTS** (local hardware item). Place connections in **OUTLET BOX**. Uninsulated wire is a **GROUND WIRE** and must be connected to a grounding terminal or a ground lead in the **OUTLET BOX**.
4. Position **BACKPLATE** over **FIXTURE SCREWS**. Secure with **KNURLED KNOBS**.
5. Hook bottom of **GLASS DIFFUSER** over **CLIP** on **BACKPLATE**. Swing **GLASS DIFFUSER** to top of **BACKPLATE** and secure with **THUMB SCREW**.

CAUTION: MAXIMUM WATTAGE MARKED ON FIXTURE MUST NOT BE EXCEEDED.

